

DocuCentre SC2020

Give your small business a big voice.



Affordable colour. Professional results.

The DocuCentre SC2020 is an affordable solution that gives you all the functionality of an A3 multifunction device with the added benefit of vibrant colour so you can stand out from the crowd.

Quality Colour

Enhance your image with colour

The ability to print high quality colour enhances the way your company is represented. Bringing colour printing in-house provides more control, improves cashflow, and enables more flexibility when it comes to marketing your business.

High quality colour

Fuji Xerox has developed a high-precision, S-LED (Self-Scanning Light Emitting Diode) print head technology that achieves an output resolution of 1200 x 2400 dpi.

High-speed colour correction

IReCT (Image Registration Control Technology) is a digital image registration control technology providing the ultra high precision of 2400 dpi. This ensures highly accurate dot placement resulting in outstanding print quality.

Advanced toner

The DocuCentre SC2020 uses EA-Eco toner. which is manufactured using emulsion aggregation technology to form toner particles that are smaller and more uniform than conventional toners, producing a much higher image quality.

Productivity and Efficiency

Maximise staff productivity

Fuji Xerox has leveraged their renowned design and innovation, and put it into a powerful desktop device. A device on a desk can free up expensive office space, and/or enables decentralised workgroup printing so that staff can collect prints from a device placed at arms-length (rather than walking half-way across the office), and continue working.

ID card copy

The ID card copy feature allows you to copy both sides of the card onto the same side of the paper. Simply place an ID card on the copier platen, press the ID card copy button and follow the directions on the 4.3 inch touch screen. A complex job made easy.

Print and Scan from mobile devices

Printing and scanning to and from your mobile device is achievable via the 'Print Utility', which is available as a free download for iOS and Android devices.


Print web pages, photos, emails and more, directly from your mobile device. You can also scan documents and send to your mobile device directly from the DocuCentre SC2020.*

Copy 4 pages onto 1 sheet of paper

Users can copy 2 pages of a document onto one side of paper (2-up). When you combine this with the duplex feature, four pages can be copied onto both sides of a single sheet.

Clever fax forwarding (optional)

Faxes you receive can be uploaded to a server or sent to registered e-mail addresses, eliminating the need to print each fax.



Control your print environment

The Auditron feature allows you to control print output by setting usage permissions for all users. For instance, you could give registered users the ability to print in colour, and limit the number of pages that can be printed. Unregistered users can be restricted to printing only in monochrome, and prevented from all copying.





 $Print\ Utility\ for\ iOS\ and\ Print\ Utility\ for\ Android\ can\ be\ downloaded\ from\ the\ App\ Store\ and\ Google\ Play\ respectively.$

Ouick Facts DocuCentre SC2020

- Print-Copy-Scan-Email-Fax*
- Copy/Print Speed: up to 20ppm
- Print Resolution: 1200 x 2400dpi
- Duplex Automatic Document Feeder
- 4.3 inch colour touch-screen
- Dimensions: W 595 x D 586 x H 634 mm
- Weight: 49kg





Ideal for small workgroups seeking a compact, affordable A3 colour printer with multifunction capabilities

Sustainability

EA-Eco Toner

Our EA-Eco Toner with low-melt technology achieves minimum fusing temperature at 20°C less than conventional toner for significant energy savings.

Toner save mode

The toner saving function has three settings allowing you to manage your toner usage by choosing the toner setting best suited to your needs. For example, for internal documents that may not need high image quality, simply select 'light' or 'lightest' to save toner.

Low running costs

Proven S-LED print engine technology combined with EA-Eco toner consumes minimal energy, meaning lower running costs for you and a greener planet for us all.

ENERGY STAR compliant

This DocuCentre SC2020 conforms to the International ENERGY STAR Program, which considers environmental issues, such as climate change, with a focus on developing and implementing energy-efficient office automation equipment.



Ease of Use

Easy to replace consumables

There's no need to rotate or move the printer to perform routine maintenance. Replacement of toners and drum unit is easy, via the printer's frontside access panel.

Intuitive user interface

The 4.3-inch, colour touch-screen interface with its big, bright icons is easy to use, and intuitive menus make walk-up operation fast and easy.

Reliability

Less paper jams

Improved paper path enables the use of a wider range of paper with higher reliability.

Advanced print head technology

The S-LED print head has fewer moving parts than a conventional laser printer, ensuring ultra-quiet operation, reduced energy usage and a high level of operational reliability.



Other convenient features

- 1 Fax Kit*
- 2 Duplex copying and printing
- 3 Duplex Auto Document Feeder Copying and scanning is fast and efficient thanks to the Duplex Automatic Document Feeder
- 4 One tray module* 500 sheet tray

* Optional

DocuPrint SC2020 shown with optional one tray module



DocuCentre SC2020 Specifications

Basic Specifications / Copy Function

Item		Description	
Туре		Desktop	
Memory Capacity		512 MB (Max. 512 MB)	
Hard Disk Capacity		_	
Colour Capability		Full colour	
Scan Resolution		600 x 600 dpi	
Print Resolution		Output resolution : True 1200 x 2400 dpi	
Warm-up Time		39 seconds or less (At room temperature 20 °C)	
Original Size		Maximum of 297 x 432 mm (A3, 11 x 17") for both Sheet and Book	
	Мах.	A3, 11 x 17"	
Paper Size	Min.	A5 (Bypass Tray : Non-standard size : 89 × 98 mm)	
Paper Size	Image Loss Width	Lead edge 5.5 mm or less, trail edge 5.5 mm or less, right / left edge 5.5 mm or less	
Paper	Tray	Tray 1: 60 to 90 gsm, Tray 2(Optional): 60 to 256 gsm	
Weight*1	Bypass Tray	60 to 216 gsm	
First Copy Output Time		Monochrome: 8.6 seconds (A4 LEF / Monochrome priority mode) Colour: 10.8 seconds (A4 LEF / Colour priority mode)	
Continuous	A4 LEF	Monochrome: up to 20 ppm, Colour: up to 20 ppm	
Copy Speed*2	A4, B4, A3, B5 LEF / B5	Monochrome : up to 12 ppm, Colour : up to 12 ppm	
Paper Tray	Standard	Tray 1 : 250 sheets*3 Bypass Tray : 80 sheets*4	
Capacity	Optional	Tray 2: 500 sheets*3	
	Мах.	830 sheets (Main Unit + One Tray Module)	
Output Tray	/ Capacity	250 sheets (A4)*3	
Power Source	ce	AC 220 - 240 V ±10 %, 5 A, 50 / 60 Hz common	
Power Consumption		220 V : 1.1 kW or less, 240 V : 1.2 kW or less Sleep Mode : 1.4 W or less, Low Power Mode : 46 W or less, Ready Mode : 78 W or less	
Dimensions		W 595 x D 586 x H 634 mm (with document feeder)	
Weight*5		49 kg (with document feeder + Duplex Output Unit)	
Warranty		Three (3) year on-site warranty including a Premium Guarantee	

^{*1:} It is recommended to use Fuji Xerox recommended paper. Correct print output may not be possible depending on the requirement. *2: The speed may be reduced due to the image quality adjustment. *3: When using 80 gsm paper. *4: When using 80 gsm paper. *5: Excluding Toner Cartridge.

Print Function

rinit i diletion				
Item		Description		
Continuous Print Speed		Same as the Basic Specifications / Copy Function		
Print Resolution*1	Output Resolution	True 1200 x 2400 dpi		
	Data Process Resolution*3	600 x 600 dpi		
Page Description Language		PCL6 / PCL5e, HBPL		
Operating System* ²	PCL6 Driver (Standard)	Windows® XP (32bit), Windows Server® 2003 (32bit) Windows Vista® (32bit), Windows Server® 2008 (32bit) Windows® 7 (32bit), Windows® 8 (32bit) Windows® 8.1 (32bit), Windows® XP Professional (64bit) Windows Server® 2003 (64bit), Windows Vista® (64bit) Windows Server® 2008 (64bit), Windows® 7 (64bit) Windows Server® 2008 R2 (64bit), Windows® 8 (64bit) Windows Server® 2012 (64bit), Windows® 8.1 (64bit) Windows Server® 2012 R2 (64bit)		
	Mac OS X-Driver (Standard)	Mac OS X 10.5 / 10.6 / 10.7 , OS X 10.8 / 10.9		
Interface		Ethernet 100BASE-TX / 10BASE-T, USB 2.0		

 $^{^{*1}}$: The speed may be reduced due to the image quality adjustment. The speed may also be reduced depending on the document attributes. *2 : Please refer to the Fuji Xerox website for the latest supported operating systems. *3 : The data process or driver resolution is set to 600dpi to better manage file sizes across the network. Output resolution is still true 1200 x 1200 ye 1200 c.

- Notes
 1) If the storage media (such as hard disk drives) of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall Fuji Xerox be liable for any damages whatsoever ar from loss of data.
- 2) Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

 3) The product specifications, appearance and other details in this catalog are subject to change without notice for improvements.

Other company names or product names are registered trademarks or trademarks of each company.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc. Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

For Your Safety

For Your Satety Before using the product, read the Instruction Manual carefully for proper use. Use the product with the power source and voltage specified. Be sure to establish ground connection. Otherwise, electronic shock may result in the case of a failure or short circuit.

For more information or detailed product specification, please call or visit us at

Fuji Xerox Asia Pacific Pte Ltd

14a Rodborough Road Frenchs Forest NSW 2086 Australia 1300 793 769 New Zealand 0800 993 769

www.fujixeroxprinters.com.au www.fujixeroxprinters.co.nz

Scan Function

Item		Description	
Туре		Colour Scanner	
Scan Resolution	TWAIN	Monochrome and greyscale : 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi, 150 x 150 dpi Colour : 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi, 150 x 150 dpi	
	WIA	Colour, monochrome and greyscale : 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi, 150 x 150 dpi	
Scanning Speed*		Monochrome : up to 24 ppm, Colour : up to 19 ppm [Fuji Xerox standard paper (A4 LEF), 200 dpi]	
Interface		Ethernet 100BASE-TX / 10BASE-T, USB 2.0	

Note: WIA stands for Windows Imaging Acquisition. * The scanning speed varies depending on the documents.

Duplex Automatic Document Feeder

Item	Description	
Original Size / Paper Weight	Max.: A3, 11 x 17" Min.: A5 (Non-standard size: 125 x 125 mm) 38 to 128 gsm (2 Sided: 50 to 128 gsm)	
Capacity*	110 Sheets	
Feeding Speed (A4 LEF Simplex)	Monochrome : up to 20 ppm , Colour : up to 18 ppm	

^{* 80} gsm paper

Fax Function (Optional)

Description	
Max: A3, 11 x 17"	
Max : A3, 11 x 17" Min : A5	
2 seconds and more but fewer than 3 seconds*	
ITU-T G3	
Telephone subscriber line, PBX, Fax communication (PSTN), Max. 1 port	

^{*}When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines / mm) and in high-speed mode (28.8kpps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

One Tray Module (Optional)

Item	Description
Paper Size	Same as the Basic Functions / Copy Function
Paper Weight	60 to 256 gsm
Paper Feed Capacity*	500 sheets
Dimensions	W 541 x D 586 x H 113 mm
Weight	11 kg

^{* 80} gsm paper

Consumables

Item	Code	Yield
Toner Cartridge (K)*1	CT202246	9,000
Toner Cartridge (Y)*1	CT202249	3,000
Toner Cartridge (M)*1	CT202248	3,000
Toner Cartridge (C)*1	CT202247	3,000
Conversion Cartridge (K) (Enables Metering)	CT202237	9,000
Toner Cartridge (K) Metered*1	CT202238	9,000
Toner Cartridge (Y) Metered*1	CT202241	3,000
Toner Cartridge (M) Metered*1	CT202240	3,000
Toner Cartridge (C) Metered*1	CT202239	3,000
Waste Toner Bottle*2	CWAA0869	15,000
Drum Cartridge (CMYK)*2	CT351053	76,000

^{*1 :} Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used. *2 : Average standard pages. Yield will vary depending on job run length, media size and orientation.

The device ships with starter toner cartridges. The black toner yield is 4,000 pages, and each colour toner yield is 2,500 pages (see points 1 and 2 above regarding yields)